

Affordable Price. Durable Design.

Features at a glance:

- Increased capacity for greater production
- Simple, single motor design offers smooth operation
- Three control options based on your needs
- Three speeds deliver advantages over two-speed models (E and X models only)
- Six speeds offer increased advantages in washing (J models only)
- Proper cylinder and rib design for enhanced mechanical action factor, wash/rinse quality
- Soap chute and liquid soap connectors standard
- Durable, galvanized steel frame (stress is spread evenly)
- Bearings aligned in rigid housing
- Double water seals protect bearings
- 5/3 Warranty Plan
- Fit through standard 3' - 0" door (excluding MWR36J4)

Specifications

	• MWT12E5	• MWT16E5		• MWT27E5		
	• MWT12X5	• MWT16X5	• MWT18E4	• MWT27X5		
	• MWT12J5	• MWT16J5	• MWT18X4	• MWT27J5	• MWR36J4	
Maximum Capacity—lb. (kg)*	25 (12)	35 (16)	45 (20)	45 (20)	60 (27)	80 (36)
Cylinder diameter—in. (mm)	23 (575)	23 (575)	28 (700)	28 (700)	30 (762)	36 (915)
Cylinder depth—in. (mm)	14 (347)	18 (449)	18 (468)	18 (468)	22 (559)	21 (533)
Gross cylinder vol cu. Ft. (L)	3.18 (90)	4.2 (117)	6.36 (180)	6.36 (180)	9.0 (255)	12.37 (350)
Door Opening—in. (mm)	12 (304)	12 (305)	15.7 (399)	15.7 (399)	15.7 (399)	21.7 (551)
Motor—HP	1	1.5	3	3	4	5.5
Wash Speed—RPM **	43	43	39	39	38	34
Distribution Speed—RPM**	90	90	71	71	65	63
Extract—RPM**	530	530	480	620	485	442
Maximum Extract G Forces	90	90	90	150	100	100
Drain Valve—in. (mm)	2 (51)	2 (51)	3 (76)	3 (76)	3 (76)	3 (76.2)
Inlet connection—in. (mm)	0.75 (19)	0.75 (19)	0.75 (19)	0.75 (19)	0.75 (19)	0.75 (19)
Overall width—in. (mm)***	29 (736)	29 (736)	34.45 (875)	34.45 (875)	34.45 (875)	40.29 (1023)
Overall depth—in. (mm)***	36.31 (922)	42.13 (1070)	47.41 (1204)	47.41 (1204)	51.75 (1314)	52.13 (1324)
Overall height—in. (mm)***	43.19 (1097)	43.19 (1097)	52.70 (1339)	52.70 (1339)	56.25 (1429)	60.81 (1545)
Approximate gross weight—lb. (kg)***	536 (243)	581 (265)	816 (370)	984 (446)	1164 (528)	1235 (560)

*Depending on density and soil content of goods **Approximate

***With standard accessories Specifications and appearance subject to change without notice. Contact factory for acoustics data.



Pellerin Milnor Corporation
P.O. Box 400, Kenner, LA, 70063, USA
Phone: (504) 467-9591
(800) 469-8780
www.milnor.com
milnorinfo@milnor.com

Printed in the USA
© Pellerin Milnor Corporation
Brochure B22SL17001/17516