

SPECIFICATIONS

	MPI540		MPI556		MPI640		MPI650		MPI656		MPIA50	
Batch Size - lb. (kg)	110	(50)	110	(50)	150	(68)	150	(68)	150	(68)	260	(118)
Nominal cake diameter - in. (mm)	36	(914)	36	(914)	39.37	(1000)	39.37	(1000)	39.37	(1000)	48	(1219)
Standard min. cycle time** - secs	75	-	75	-	75	-	75	-	75	-	90	-
Maximum pressure - psi (bar)	580	(40)	812	(56)	580	(40)	725	(50)	812	(56)	725	(50)
Hydraulic pump motor - HP (kW)	15	(11.19)	15	(11.19)	15	(11.19)	30	(22.37)	30	(22.37)	40	(29.83)
Recirculation motor - HP (kW)	1.5	(1.12)	1.5	(1.12)	1.5	(1.12)	1.5	(1.12)	1.5	(1.12)	1.5	(1.12)
Conveyor motor - HP (kW)	1	(.75)	1	(.75)	1	(.75)	1	(.75)	1	(.75)	1	(.75)
Overall width* - in. (mm)	104.25	(2648)	104.25	(2648)	104.25	(2648)	104.25	(2648)	104.25	(2648)	116.94	(2970)
Overall depth* - in. (mm)	93.06	(2363)	93.06	(2363)	93.06	(2363)	93.06	(2363)	93.06	(2363)	115.03	(2922)
Overall height* - in. (mm)	150.25	(3816)	151.75	(3854)	151.75	(3854)	153.75	(3905)	153.75	(3905)	179.38	(4556)
Gross weight* - lb. (kg)	24,680	(11195)	28,725	(13030)	29,140	(13218)	33,140	(15032)	33,310	(15109)	49,680	(22534)

**Special options required for 90 seconds or faster transfer times.

Specifications and appearance subject to change without notice. Contact factory for acoustics data and exact specifications. All dimensions are Center discharge models unless otherwise noted. *Approximate, with standard accessories.

Another Milnor extraction option:



Centrifugal extractor: Excellent for garments, dust mats, 100% polyester textiles (including surgery and barrier cloth items), plus cottons and blends.

Also available: Ram Command™ press ram option for single stage presses:

This feature enhances the control over the ram's descent into the can. It also allows the ram to descend at a slower rate (programmable for goods type) when pressing delicate goods. For example, high thread-count cotton sheets or barrier material that are subject to fabric microbursting would benefit from this unique feature.

Material Handling Devices also available:

