



Maximum Performance



**YOUR LIFE-SAVING DUTIES  
DON'T STOP ON THE FIREGROUND**

UNIMAC.COM

**UW45 & UW65 POCKET HARDMOUNT WASHER EXTRACTOR**



# KEEP YOUR GEAR **AND** YOUR WASH RECORDS SPOTLESS

You have bigger fires to put out than equipment record keeping, but new safety recommendations encourage protecting your company by washing PPE *after every fire*. The new UniMac UW45 washer extractor not only **has a customized spin cycle that won't damage PPE**, it's also compatible with the cloud-based **FireLinc™ application**, which lets safety officers easily maintain a full gear-washing history for each member of their team. FireLinc works with your inventory tracking system and sorts data by the equipment ID, where it was washed and even who washed it. You focus on safety. FireLinc will fill in the details.


**FireLinc**™

# FIREHOUSE CUSTOMIZATION WITHOUT SACRIFICING ANY OF THE UW-SERIES FEATURES USERS DEPEND ON...


## THE OPTISPRAY™ ADVANTAGE

LESS WATER. SUPERIOR RINSING. MAXIMUM THROUGHPUT.

New OPTIspray Rinsing Technology takes improved efficiency and maximized throughput to the next level. Available on all UniLinc cycles, OPTIspray combines fire hose-like, spray-rinsing power with wash chemistry to attack dirt and stains, washing them away and down the drain. Unlike bath rinses, which simply dilute wash chemistry and leave garments soaking in contaminants.



OPTISPRAY



NORMAL RINSE

**39%**

### WATER SAVINGS

Get a quality wash while using as much as 39% less water than competitor brands.

**12%**

### SHORTER CYCLE TIMES

Decrease cycle rinse times by up to 12%.

**\$2,110**

### LOWER UTILITIES

Save up to \$2,110 in yearly utilities compared to competitor brands.

**22%**

### BETTER RINSING

Leaves 22% less residual wash chemistry compared to the nearest competitor.



### PPE-CUSTOMIZED SPIN CYCLE

The 100G spin cycle is specially designed for safe, effective washing of PPE.



**OUR UNILINC™  
CONTROLS ARE  
REVOLUTIONIZING THE  
WAY PEOPLE THINK  
ABOUT LAUNDRY.**

**SAVE WATER AND ENERGY  
INCREASE THROUGHPUT  
GAIN FLEXIBILITY AND CONTROL  
MONITOR YOUR LAUNDRY  
EASY TO USE  
WIRELESS NETWORKING  
48 PROGRAMMABLE CYCLES**



## UW45 AND 65 HARDMOUNT WASHER EXTRACTORS-UNILINC CONTROL

| SPECIFICATIONS                       | UW45         | UW65        |             |
|--------------------------------------|--------------|-------------|-------------|
| Control Options                      | UniLinc™     | UniLinc™    |             |
| Capacity - lb (kg)                   | 45 (20)      | 65 (30)     |             |
| Cylinder Diameter - in (mm)          | 31 (787)     | 31 (787)    |             |
| Cylinder Depth - in (mm)             | 16.6 (422)   | 22.1 (561)  |             |
| Cylinder Volume - cu ft (liters)     | 7.3 (207)    | 9.7 (275)   |             |
| Height - in (mm)                     | 64.7 (1643)  | 64.7 (1643) |             |
| Width - in (mm)                      | 34.1 (866)   | 34.1 (866)  |             |
| Depth - in (mm)                      | 45.3 (1151)  | 51.1 (1298) |             |
| Door Opening Size - in (mm)          | 17.8 (452)   | 17.8 (452)  |             |
| Door Bottom to Floor - in (mm)       | 21.4 (544)   | 21.4 (544)  |             |
| Motor Size - HP (kW)                 | 5 (3.7)      | 5 (3.7)     |             |
| Total # of Speeds                    | L Sp<br>5    | L Sp<br>5   |             |
| Cylinder Speed<br>RPM ( G-Force)     | Gentle       | 30 (0.4)    | 30 (0.4)    |
|                                      | Wash         | 42 (0.78)   | 42 (0.78)   |
|                                      | Distribution | 75 (2.5)    | 75 (2.5)    |
|                                      | Very Low     | 248 (27)    | 248 (27)    |
|                                      | Low          | 477 (100)   | 477 (100)   |
| Drain Diameter - in (mm)             | 3 (76)       | 3 (76)      |             |
| Steam Connection - in (mm)           | ½ (13)       | ½ (13)      |             |
| Water Inlet Connection - in (mm)     | 4 @ ¾ (19)   | 4 @ ¾ (19)  |             |
| Shipping<br>Dimensions -<br>in (mm)  | Width        | 37.2 (945)  | 37.2 (945)  |
|                                      | Depth        | 53.8 (1370) | 53.8 (1370) |
|                                      | Height       | 65 (1650)   | 65 (1650)   |
| Net Weight - lb (kg)                 | 1080 (490)   | 1110 (499)  |             |
| Standard Shipping Weight - lb (kg)   | 1120 (508)   | 1150 (522)  |             |
| Slat Crate Shipping Weight - lb (kg) | 1250 (567)   | 1280 (581)  |             |
| Agency Approvals                     | cULus        | cULus       |             |

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT [UNIMAC.COM](http://UNIMAC.COM)  
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

Consult your UniMac distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility have been registered to ISO 9001:2008.