

# 1. Hard-mounted Washer Extractors

## UC20, UC30, UC40, UC60, UC80, UC100

### Features and Benefits

- Reduce dry-time and increase throughput with 200 G-Force extraction speed
- Computer-optimized frame design stronger than ever before with quieter operation
- Stainless steel, top and front panel
- Three different control options (M30, M9 and M4) offer flexibility and enhanced laundry management
- Heavy-duty bearings and seals
- Engineered for quick troubleshooting and ease of service
- Self-cleaning 4-compartment dispenser
- Large heavy-duty loading door
- Standard boiler fed execution

### Options

- **M30 Control** - There are a total of 30 programs that you can modify to customize your laundry for specific needs. Special features include cycle time remaining, temperature-controlled fill, cycle counter and test-cycle for diagnostics. Also features 30 programmable water levels to reduce water use. Easily programmed through control's infrared port.
- **M9 Control** - Nine cycles that can be modified to meet your laundry's unique demands. Three water levels and up to five supply signals for automated dispensing of laundry chemicals. Cycle counter and test cycle for self-diagnostics.
- **M4 Control** - Four-cycle control for laundries with light soil and limited selection of linens. Limited diagnostic test.
- Stainless steel side panels
- Optional electrical or steam heating



SPECIFICATIONS		UC20	UC30	UC40	UC60	UC80	UC100
Control Option		M4, M9, M30	M4, M9, M30	M4, M9, M30	M4, M9, M30	M4, M9, M30	M4, M9, M30
Capacity – kg (lb)		8 (20)	12 (30)	18 (40)	26 (60)	37 (80)	43 (100)
Overall Width – mm (in)		660 (26)	737 (29)	778 (30 5/8)	865 (34 1/16)	1054 (41 1/2)	1054 (41 1/2)
Overall Depth – mm (in)		767 (30 1/4)	878 (34 9/16)	1009 (39 3/4)	1081 (42 9/16)	1308 (51 1/2)	1336 (52 5/8)
Overall Height – mm (in)		1067 (42)	1142 (45)	1199 (47 1/4)	1267 (49 7/8)	1426 (56 3/16)	1426 (56 3/16)
Cylinder Diameter – mm (in)		533 (21)	610 (24)	667 (26 1/4)	762 (30)	916 (36)	916 (36)
Cylinder Depth – mm (in)		349 (13 3/4)	406 (16)	514 (20 1/4)	559 (22)	559 (22)	660 (26)
Cylinder Volume – litres (cu. ft.)		78.1 (2.76)	118 (4.19)	180 (6.34)	255 (9.0)	354 (12.4)	434 (13 1/2)
Door Opening Size – mm (in)		295 (11 5/8)	364 (14 5/16)	413 (16 1/4)	413 (16 1/4)	470 (18 1/2)	470 (18 1/2)
Door Bottom to Floor – mm (in)		365 (14 3/8)	356 (14)	368 (14 1/2)	379 (14 15/16)	455 (17 15/16)	455 (17 15/16)
Water Inlet Connection – mm (in)		2 @ 19 (3/4)	2 @ 19 (3/4)	2 @ 19 (3/4)	2 @ 19 (3/4)	2 @ 19 (3/4)	2 @ 19 (3/4)
Drain Diameter – mm (in)		1 @ 52 (2)	1 @ 52 (2)	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)	1 @ 76 (3)
Drain Height to Floor – mm (in)		114 (4 1/2)	114 (4 1/2)	122 (4 13/16)	119 (4 11/16)	145 (5 3/4)	145 (5 3/4)
Total # of Speeds		6, 9	6, 9	6, 9	6, 9	6, 9	6, 9
Cylinder Speeds – RPM (G-Force)	Gentle	37 (0.4)	34 (0.4)	33 (0.4)	31 (0.4)	28 (0.4)	28 (0.4)
	Wash	51 (.8)	48 (.8)	46 (.8)	43 (.8)	39 (.8)	39 (.8)
	Distribution	92 (2.5)	86 (2.5)	82 (2.5)	77 (2.5)	70 (2.5)	70 (2.5)
	Very Low	301 (27)	282 (27)	269 (27)	252 (27)	230 (27)	230 (27)
	Low	518 (80)	485 (80)	464 (80)	434 (80)	396 (80)	396 (80)
	Medium	580 (100)	542 (100)	518 (100)	485 (100)	443 (100)	443 (100)
	High	648 (120)	606 (120)	579 (120)	542 (120)	495 (120)	495 (120)
	Very High	710 (150)	664 (150)	635 (150)	594 (150)	542 (150)	542 (150)
	Ultra High	819 (200)	766 (200)	733 (200)	686 (200)	626 (200)	568 (165)
Voltage wires/ Circuit Breaker – FLA	B 120/60/1	15-12	N/A	N/A	N/A	N/A	N/A
	X 200-208/220-240/50/60/3/1/3	15-6 (1 Ph) 15-4 (3 Ph)	15-7 (1 Ph) 15-5 (3 Ph)	15-10 (1 Ph) 15-6 (3 Ph)	15-11 (1 Ph) 15-8 (3 Ph)	20-16 (1 Ph) 15-11 (3 Ph)	20-16 (1 Ph) 15-11 (3 Ph)
	Q 200-208/220-240/50/60/3/3	15-5	15-5	15-6	15-8	15-11	15-11
	N 440-480/50/60/3/3	15-4	15-4	15-5	15-6	15-8	15-8
	P 380-415/50/60/3/3	15-4	15-4	15-5	15-6	15-8	15-8
Shipping Dimensions Approx. - mm (in)	Width	711 (28)	800 (31 1/2)	876 (32 1/2)	953 (37 1/2)	1118 (44)	1118 (44)
	Depth	859 (33 13/16)	973 (38 5/16)	1105 (43 1/2)	1191 (46 15/16)	1384 (54 1/2)	1486 (58 1/2)
	Height	1229 (48 7/16)	1303 (51 5/16)	1361 (53 5/8)	1430 (56 5/16)	1488 (58 5/8)	1488 (58 5/8)
Motor Power Consumption – kW (HP)		.75 (1)	.75 (1)	1.7 (2)	2.2 (3)	3.7 (5)	3.7 (5)
Net Weight – kg (lb)		152 (335)	209 (460)	249 (550)	315 (695)	549 (1210)	572 (1260)
Shipping Weight – kg (lb)		166 (365)	225 (495)	268 (590)	338 (745)	572 (1260)	594 (1310)
Slat Crate Shipping Weight – kg (lb)		204 (450)	268 (590)	313 (690)	390 (860)	628 (1380) 2	651 (1435)
*Agency Approvals		ETL <sub>us</sub> CE	ETL <sub>us</sub> CE	ETL <sub>us</sub> CE	ETL <sub>us</sub> CE	ETL <sub>us</sub> CE	ETL <sub>us</sub>