

Specifications

MODEL	Metric	US	DP-200		DP-250	
Maximum Capacity	lbs	kg	200	91	250	114
Overall Dimensions						
A - Width	inch	mm	65	1651	65	1651
B - Depth	inch	mm	79.19	2011	84	2134
C - Height (gas, non tilt)	inch	mm	101	2565	101	2565
D - Height (steam, non tilt)	inch	mm	93.38	2372	93.38	2372
Drying Cylinder Information						
Diameter	inch	mm	59	1499	59	1499
Depth	inch	mm	46.85	1190	48.82	1240
Volume	cu ft	liters	75	2123	77	2180
Door						
Door Opening Diameter	in	mm	35.43	900	35.43	900
Height to Bottom of Door	in	mm	31.75	806	31.75	806
Gas Heating						
Air Flow	CFM	cmm	5300	150	5800	164
Heat Input	BTU/hr	kcal/hr	760000	190000	950000	237500
Gas Inlet	inch	mm	1	25.4	1	25.4
Air Outlet	inch	mm	20	508	20	508
Electrical Requirements 208-230V, 50/60Hz, 3PH 380-460V, 50/60Hz, 3PH	Amp Amp	Breaker Breaker	34 15	80 40	39 18	80 40
Steam Heating						
Air Flow	CFM	cmm	6500	184	7000	198
Steam Consumption	BHP	kW	27	264.9	32	313.9
Operating Pressure	psi	bar	80-125	5.5-8.6	80-125	5.5-8.6
Steam Supply	inch	mm	2	51	2	51
Air Outlet	inch	mm	20	508	20	508
Electrical Requirements 208-230V, 50/60Hz, 3PH 380-460V, 50/60Hz, 3PH	Amp Amp	Breaker Breaker	34 15	50 25	39 18	50 25
Weight and Shipping Information						
Net Weight	lb	kg	3668	1668	3922	1782
Shipping Weight	lb	kg	3750	1705	4000	1820

Standard Features:

- Microprocessor control
- Reversing cylinder
- Heavy duty drive system
- Large door opening
- Cool down
- Overload protection
- High limit safety thermostats
- Soft start
- Stainless steel cylinder
- Rotation sensor

Optional Features:

- Variable frequency drive
- Steam heating
- Gas heating
- Air recirculating system
- Stainless steel front
- Fire suppression system
- Automatic blower cleaning
- Humidity Sensing / Autodry
- Tilt forward for unloading

Specifications and design subject to change without notice
Additional options: Consult factory

B&C Technologies
17740 Ashley Drive
Panama City Beach, FL 32413
p: 850-249-2222
f: 850-249-2226
www.bandctech.com
sales@bandctech.com

