

Specifications

MODEL	Metric	US	DI-225		DI-325		DI-475	
Maximum Capacity (dry weight)	kg	lbs	102	225	147	325	215	475
Basket Diameter	mm	inch	1620	63.78	1620	63.78	1800	70.9
Basket Depth	mm	inch	1240	48.8	1541	60.7	2000	78.8
Basket Volume	cu m	cu ft	2.55	90.26	3.17	112.2	5.1	180.1
Basket Motor	kW	HP	2.34	3	3.7	5	5.5	7.5
Blower Motor	kW	HP	11	15	15	20	18.5	25
Cabinet Size								
A - Machine Height	mm	inch	2902	114.25	3132	123.3	3033	119.4
B - Machine Depth	mm	inch	1550	61	1860	73.2	2562	100.9
C - Machine Width	mm	inch	1926	75.8	1926	75.8	3009	118.5
D - Machine Height Tilted	mm	inch	3160	124.4	3470	136.6	3497	137.7
E - Machine Depth Tilted	mm	inch	2075	81.7	2335	92	2957	116.4
Gas								
Air Flow	cmm	cfm	155	5500	184	6500	311.5	11000
Heat Input	kcal/hr	btu/hr	206640	820000	297355	1180000	718188	2850000
Gas Inlet	mm	inch	38.1	1.5	31.75	2x 1.25	5.08	2
Exhaust Duct	mm	inch	508	20	508	20	610	24
Steam								
Air Flow	cmm	cfm	198	7000	212	7500	340	12000
Steam Consumption	BHP		30		35		60	
Operating Pressure	sq kg/cm	psi	5.6-8.79	80-125	5.6-8.79	80-125	5.6-8.79	80-125
Steam Supply	mm	inch	50.8	2	50.8	2	63.5	2.5
Steam Return	mm	inch	50.8	2	50.8	2	31.75	1.25
Exhaust Duct	mm	inch	508	20	508	20	610	24
Net Weight	kg	lbs	1736	3820	1932	4250	3950	8710
Shipping Weight	kg	lbs	1800	3970	1995	4400	4030	8860
Electrical Requirements								
208-230V, 50/60Hz, 3PH	Amp	Breaker	62	100	87	125	90	125
380-460V, 50/60Hz, 3PH	Amp	Breaker	31	50	43	60	45	60


Standard Features:

- ◆ Stainless Steel Drying Cylinder
- ◆ Microprocessor Control
- ◆ Large Capacity Slide Out Lint Drawer
- ◆ Sealed Bearings
- ◆ Reversing Cylinder
- ◆ Rotation Sensor


Optional Features:

- ◆ 1 or 2 Way Tilting
- ◆ Humidity Sensing / Autodry
- ◆ Variable Frequency Drive
- ◆ Fire Suppression System
- ◆ Vertical or Horizontal Sliding Doors
- ◆ Pass Through System with Front and Rear Doors
- ◆ Side Mounted Steam Coils
- ◆ Tunnel System Integration
- ◆ Custom Controls
- ◆ Air Recirculation System
- ◆ Automatic Blower Cleaning


FRONT VIEW




SIDE VIEW



REAR VIEW



TOP VIEW



B&C Technologies
 1250 West 17th Street
 Panama City, FL 32405
 p: 850-249-2222
 f: 850-249-2226
www.bandctech.com
sales@bandctech.com