

Specifications

MODEL	Units		HP-65		HP-125	
	Metric	US				
CAPACITY:						
	kg	lbs	29.5	65	56.8	125
OVERALL DIMENSIONS:						
A - Width	mm	in	879	34.6	1295	51.0
B - Depth	mm	in	1194	47.0	1554	61.2
C - Height	mm	in	1651	65.0	1669	65.7
WEIGHT AND SHIPPING INFORMATION:						
Net weight	kg	lbs	660	1450	1489	3275
Domestic shipping weight	kg	lbs	720	1584	1505	3310
CYLINDER INFORMATION:						
Diameter	mm	in	790	31.1	1067	42
Depth	mm	in	560	22	610	24
Volume	liters	cu ft	274	9.7	540	19
CYLINDER SPEEDS:						
Wash	G	rpm	0.8	42	0.8	37
Distribution	G	rpm	2	67	3	71
Intermediate extract	G	rpm	150	583	50	290
High extract 1	G	rpm	200	673	100	410
High extract 2	G	rpm	250	753	150	502
High extract 3	G	rpm	300	825	200	579
DOOR OPENING AND HEIGHT:						
Diameter	mm	in	450	17.7	508	20
Height of door bottom above floor	mm	in	635	25	400	28
DRIVE INFORMATION:						
Number of motors	Number		1		1	
Size of motor	kW	Hp	3.7	5	7.5	10
WATER INLETS						
Hot water size	NPT		3/4		1	
Cold water size	NPT		3/4		1	
Additional water inlet	NPT		3/4		1	
DRAIN OUTLETS AND CAPACITY:						
Number of drains	Number		1		1	
Drain size	mm	in	76.2	3	76.2	3
STEAM INLET and CONSUMPTION:						
Steam inlet size	NPT		1/2		1	
ELECTRICAL SERVICE:						
208-240VAC, 50/60Hz, 1PH	Amps	Breaker	14	15	n/a	n/a
208-240VAC, 50/60Hz, 3PH	Amps	Breaker	8	15	32	40
380-480VAC, 50/60Hz, 3PH	Amps	Breaker	4	15	16	20

Due to our policy of ongoing improvements, all specifications are subject to change without notice.

Standard Features:

- ◆ All wetted parts are 304 (18/8) stainless steel
- ◆ 1 compartment supply dispenser (HP-65)
- ◆ 5 compartment supply dispenser (HP-125)
- ◆ 30 cycle microprocessor
- ◆ 300G extraction force (HP-65)
- ◆ 200G extraction force (HP-125)
- ◆ 5 degree lean back for strength and easier loading
- ◆ Built in vacuum breaker
- ◆ Variable speed inverter drive
- ◆ Wetcleaning functionality built in - no special options required

Optional Features:

- ◆ 5 compartment supply dispenser (HP-65)
- ◆ Extra water inlet
- ◆ Extra drain
- ◆ Steam heating
- ◆ Electric heating
- ◆ Ozone system integration



B&C Technologies
Panama City Beach, Florida
p: 850-249-2222
f: 850-249-2226
www.bandctech.com
sales@bandctech.com

