

Specifications

MODEL	Metric	US	SA-275		SA-300		SA-475	
Maximum Capacity	kg	lbs	125	275	136	300	216	475
Overall Dimensions								
A - Width (cabinet)	mm	in	1886	74.25	1886	74.25	2115	83.27
Width (maximum)	mm	in	2064	81.25	2064	81.25	2615	102.95
B - Depth	mm	in	2248	88.5	2350	92.5	2270	89.37
C - Height	mm	in	2261	89	2261	89	2540	100
Wash Cylinder Information								
Cylinder Diameter	mm	in	1321	52	1321	52	1625	64
Cylinder Depth	mm	in	864	34	965	38	1028	40.25
Cylinder Volume	liters	cu ft	1184	41.8	1323	46.7	2131	75.3
Motor								
Size	kW	HP	18.75	25	22.5	30	29	40
Cylinder Speeds (Programmable)								
Wash	G	rpm	0.8	33	0.8	33	0.8	30
Distribution	G	rpm	2	60	2	60	2	57
Intermediate Extract	G	rpm	80	330	80	330	80	287
High Extract 1	G	rpm	140	435	140	435	140	406
High Extract 2	G	rpm	218	545	218	545	218	469
High Extract 3	G	rpm	320	660	320	660	320	590
Door Opening								
Door Opening Diameter	mm	in	1020	40.2	1020	40.2	1020	40.2
Height to Bottom of Door	mm	in	876	34.5	876	34.5	653	25.7
Drain System								
Overflow Size	mm	in	64	2.5	64	2.5	64	2.5
Drain Outlet Size	mm	in	102	4	102	4	203	8
Number of Drains	Standard	Optional	1	2	1	2	1	2
Steam Inlet								
Connection Size	NPT		1		1		1-1/4	
Water Inlet								
Connection Size	NPT		1-1/4		1-1/4		1/2/1900	
Number of Inlets	Standard	Optional	2	2	2	2	2	2
Chemical Supply System								
Number of Dry Chemical Compartments	Standard	Optional	0	5	0	5	0	5
Number of Liquid Supply Connections	Standard	Optional	5	5	5	5	5	5
Liquid Supply Connection Size	NPT		1/2		1/2		1/2	
Weight and Shipping Information								
Net Weight	kg	lbs	4300	9460	4743	10435	8825	19414
Domestic Shipping Weight	kg	lbs	4345	9560	4800	10560	9120	20062

Standard Features:

- ◆ Heavy duty construction
- ◆ All wetted parts are 304 (18/8) stainless steel
- ◆ 40 inch door opening
- ◆ 30 cycle microprocessor
- ◆ 320G extraction force
- ◆ 3 degree lean back for strength and easier loading
- ◆ Air operated door gasket
- ◆ Variable speed inverter drive
- ◆ Dry zone bearings
- ◆ Standard 2 way tilt
- ◆ Stainless steel panels
- ◆ Water reuse capable
- ◆ Direct steam heating

Optional Features:

- ◆ Water reuse inlet and drain
- ◆ EMI filter
- ◆ PC programming kit

B&C Technologies

1250 West 17th Street
Panama City, FL 32405
p: 850-249-2222
f: 850-249-2226
www.bandctech.com
sales@bandctech.com