80LB CAPACITY VENDED WASHER-EXTRACTOR

PRODUCT SPECS

Capacity Ibs 80 Cylinder Diameter inch 32.5 Cylinder Depth inch 23.5 Cylinder Volume cu ft 11.3 Net Weight Ibs 1499 Crated Weight Ibs 1583 Machine Width inch 41.5 Machine Depth inch 50.9 Machine Height inch 59.1 Door Opening inch 16.8 Floor to Door inch 23.6 Shipping Dimensions inch WXDXH 42.3 x 52 x 65.2 Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted Ibs 1850 Dynamic Force Transmitted Ibs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 3W+G, 15 Amp 240/60/3 3W+G, 15 Amp 340/60/3 3W+G, 10 Amp Drain Diameter inch 3 Water Inlets inch 2 @ 3/4	PRODUCT SPECS	
Cylinder Depth inch 23.5 Cylinder Volume cu ft 11.3 Net Weight Ibs 1499 Crated Weight Ibs 1583 Machine Width inch 41.5 Machine Depth inch 50.9 Machine Height inch 59.1 Door Opening inch 16.8 Floor to Door inch 23.6 Shipping Dimensions inch WXDXH 42.3 x 52 x 65.2 Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted Ibs 1850 Dynamic Force Transmitted Ibs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 3W+G, 15 Amp 240/60/3 3W+G, 15 Amp 3W+G, 15 Amp 340-480/60/3 3W+G, 10 Amp	Capacity <i>lbs</i>	80
Cylinder Volume cu ft Net Weight Ibs 1499 Crated Weight Ibs 1583 Machine Width inch 41.5 Machine Depth inch 50.9 Machine Height inch 59.1 Door Opening inch 16.8 Floor to Door inch 23.6 Shipping Dimensions inch WxDxH Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted Ibs Dynamic Force Transmitted Ibs 1850 Dynamic Force Transmitted Ibs Available Voltages / Wire Conductor / Amp 208/60/3 240/60/3 3W+G, 15 Amp 3W+G, 15 Amp 3W+G, 10 Amp Drain Diameter inch 3	Cylinder Diameter inch	32.5
Net Weight Ibs 1499 Crated Weight Ibs 1583 Machine Width Inch 41.5 Machine Depth Inch 50.9 Machine Height Inch 59.1 Door Opening Inch 16.8 Floor to Door Inch 23.6 Shipping Dimensions Inch WXDXH 42.3 x 52 x 65.2 Washing Speeds Ipm 42 Spin Speeds Ipm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted Ibs 1850 Dynamic Force Transmitted Ibs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 240/60/3 3W+G, 15 Amp 440-480/60/3 3W+G, 15 Amp 340-480/60/3 3W+G, 10 Amp	Cylinder Depth inch	23.5
Crated Weight Ibs 1583 Machine Width Inch 41.5 Machine Depth Inch 50.9 Machine Height Inch 59.1 Door Opening Inch 16.8 Floor to Door Inch 23.6 Shipping Dimensions Inch WxDxH 42.3 x 52 x 65.2 Washing Speeds Inch 42 Spin Speeds Inch 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted Ibs 1850 Dynamic Force Transmitted Ibs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 240/60/3 3W+G, 15 Amp 340-480/60/3 3W+G, 15 Amp 340-480/60/3 3W+G, 10 Amp	Cylinder Volume cu ft	11.3
Machine Width inch Machine Depth inch Machine Depth inch 50.9 Machine Height inch 59.1 Door Opening inch 16.8 Floor to Door inch 23.6 Shipping Dimensions inch WxDxH Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs Dynamic Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp 208/60/3 240/60/3 3W+G, 15 Amp 3W+G, 15 Amp 3H-G, 10 Amp Drain Diameter inch 3	Net Weight Ibs	1499
Machine Depth inch Machine Height inch Door Opening inch Floor to Door inch Shipping Dimensions inch WxDxH Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs Basic Force Transmitted lbs Dynamic Force Transmitted lbs Available Voltages / Wire Conductor / Amp 208/60/3 240/60/3 3W+G, 15 Amp 3440-480/60/3 3W+G, 10 Amp Drain Diameter inch	Crated Weight Ibs	1583
Machine Height inch 59.1 Door Opening inch 16.8 Floor to Door inch 23.6 Shipping Dimensions inch WxDxH 42.3 x 52 x 65.2 Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 240/60/3 3W+G, 15 Amp 440-480/60/3 3W+G, 15 Amp Drain Diameter inch 3	Machine Width inch	41.5
Door Opening inch Floor to Door inch Shipping Dimensions inch WxDxH Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs Dynamic Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp 208/60/3 240/60/3 3W+G, 15 Amp 3440-480/60/3 3W+G, 10 Amp Drain Diameter inch 3	Machine Depth inch	50.9
Floor to Door inch 23.6 Shipping Dimensions inch WxDxH 42.3 x 52 x 65.2 Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 3W+G, 15 Amp 3W+G, 15 Amp 3W+G, 15 Amp 3W+G, 10 Amp Drain Diameter inch 3	Machine Height inch	59.1
Shipping Dimensions inch WxDxH 42.3 x 52 x 65.2 Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 3W+G, 15 Amp 340-480/60/3 3W+G, 15 Amp 3W+G, 10 Amp Drain Diameter inch 3	Door Opening inch	16.8
WxDxH 42.5 x 52 x 65.2 Washing Speeds rpm 42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 240/60/3 3W+G, 15 Amp 440-480/60/3 3W+G, 15 Amp Drain Diameter inch 3	Floor to Door inch	23.6
Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 3W+G, 15 Amp 208/60/3 3W+G, 15 Amp 240/60/3 3W+G, 15 Amp 440-480/60/3 3W+G, 10 Amp Drain Diameter inch 3		42.3 × 52 × 65.2
G-force 3.17/52/130/225/400 Static Force Transmitted <i>lbs</i> 1850 Dynamic Force Transmitted <i>lbs</i> 412 Frequency of Dynamic Force <i>Hz</i> 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 3W+G, 15 Amp 3440-480/60/3 3W+G, 10 Amp Drain Diameter <i>inch</i> 3	Washing Speeds <i>rpm</i>	42
Static Force Transmitted <i>lbs</i> 1850 Dynamic Force Transmitted <i>lbs</i> 412 Frequency of Dynamic Force <i>Hz</i> 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 3W+G, 15 Amp 240/60/3 3W+G, 15 Amp 440-480/60/3 3W+G, 10 Amp Drain Diameter <i>inch</i> 3	Spin Speeds rpm	83/335/530/698/931
Dynamic Force Transmitted Ibs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 3W+G, 15 Amp 3W+G, 15 Amp 440-480/60/3 3W+G, 10 Amp Drain Diameter Inch 3	G-force	3.17/52/130/225/400
Frequency of Dynamic Force <i>Hz</i> 15.5 Available Voltages / Wire Conductor / Amp 208/60/3 3W+G, 15 Amp 240/60/3 3W+G, 15 Amp 440-480/60/3 3W+G, 10 Amp Drain Diameter <i>inch</i> 3	Static Force Transmitted <i>lbs</i>	1850
Available Voltages / Wire Conductor / Amp 208/60/3 3W+G, 15 Amp 240/60/3 3W+G, 15 Amp 440-480/60/3 3W+G, 10 Amp Drain Diameter <i>inch</i> 3	Dynamic Force Transmitted <i>lbs</i>	412
208/60/3 3W+G, 15 Amp 240/60/3 3W+G, 15 Amp 440-480/60/3 3W+G, 10 Amp Drain Diameter inch 3	Frequency of Dynamic Force Hz	15.5
	208/60/3 240/60/3	3W+G, 15 Amp 3W+G, 15 Amp
Water Inlets inch 2 @ 3/4	Drain Diameter inch	3
	Water Inlets inch	2 @ 3/4
Recommended Water Pressure <i>PSI</i> 30-60	Recommended Water Pressure PSI	30-60
Water Flow gal/min 16	Water Flow gal/min	16
Total Power <i>kW</i> 4.2	Total Power kW	4.2
Electric Heating Power (optional) kW 20.7	Electric Heating Power (optional) kW	20.7

^{*} Specifications subject to change without notice or obligation. Contact Continental Girbau at (800) 256-1073 for dimensions not shown or for clarification.







