

CONTINENTAL
GIRBAU®



ECON-O-WASH & ECON-O-DRY FOR ON-PREMISE LAUNDRIES

Used as a team, the Econ-O-Wash top-load washer and the Econ-O-Dry singleload or stacked dryer effectively clean and dry smaller loads quickly and efficiently—improving on-premise laundry productivity.

GWNMN | JDE807 | JDG809 | JSEMNI | JSGMN

ECON-O-WASH TOP-LOAD WASHERS AFFORDABLE EFFICIENCY

DURABILITY

The Econ-O-Wash topload is constructed for unmatched longevity. It features a durable porcelain enamel washtub, a scratch-resistant, hard-baked porcelain enamel top and lid, a heavy-duty, two-speed motor, and a corrosion-resistant polypropylene pump—all wrapped up in a rugged galvanized steel cabinet!

ENERGY EFFICIENCY & HIGH SPIN SPEED

Unlike most home-style top-load washers, which guzzle around 40 gallons of water per load, The Econ-O-Wash topload is engineered with a water saving feature that uses just 27.3 gallons per load! By using less water, on-premise laundries significantly cut hot water consumption—saving energy and lowering utility costs! Moreover, the washer delivers 710 RPM spin speeds to remove more water from every load. In doing so, dry time is reduced—increasing productivity and reducing utility costs! The Econ-O-Wash topload offers superior energy efficiency. At start-up the machine draws fewer amps—conserving additional electricity. No wonder this washer conforms to the Department of Energy (DOE) 2013 efficiency standards.

QUALITY OF THE WASH

Superior engineering means laundry gets cleaner. The Econ-O-Wash topload features a curved, four-vane polypropylene agitator with a 210 degree agitator stroke—the longest in the industry. The machine's lengthy stroke delivers increased wash action thereby generating superb wash results.

AUTOMATIC BALANCE SYSTEM

Designed to automatically adjust out-of-balance loads, Econ-O-Wash completes wash cycles quietly, smoothly and without interruption. The liquid-filled balance ring at the top of the tub and the washer's advanced suspension design combine to eliminate interrupted wash cycles due to out-of-balance loads. The feature also eliminates the need for an out-of-balance switch!

USER-FRIENDLY CONTROL

Econ-O-Wash makes it easy for laundry room attendants to select from several wash cycles. The user simply chooses a cycle—normal, permanent press, delicate, or one of three unique energy-saving cycles—and presses start. It offers three water temperature options for the wash cycle—hot, warm and cold—along with an indicator light that illuminates when the machine is in use.



Four Vane Agitator



Automatic Balance System



Heavy-Duty Drain Hose



User-Friendly Control

ECON-O-WASH PRODUCT SPECIFICATIONS

GWNMN

Cylinder Volume	cu ft (dm ³)	3.26 (92.3)
Net Weight	lbs (kg)	190 (86)
Crated Weight	lbs (kg)	210 (95)
Machine Width	inch (mm)	25.63 (651)
Machine Depth	inch (mm)	28 (711)
Machine Height	inch (mm)	43 (1092)
Floor to Work Surface	inch (mm)	36 (914)
Shipping Dimensions	inch (mm)	28 x 30 x 45 (711 x 762 x 1143)
Water Consumption	gal (l)	27.3 (103.3)
Hot Water Consumption	gal (l)	2.3 (8.7)
Washing Speed	rpm high/low	67/44
Spin Speed	rpm high/low	710/473
Drain Diameter	inch (mm)	1 1/2 (38.1)
Water Inlets	inch (mm)	3/4 (19)
Recommended Water Pressure	PSI (bar)	20-120 (1.4/8.3)
Water Flow	gal/min (l/min)	37.5 (140)
Motor Power	Hp	1/2



MEF
Modified Energy
Factor
(cubic feet per kilowatt
hour per cycle)

1.65

WCF
Total Water
Consumption Factor
(gallons per cycle
per cubic feet)

8.4

* Modified Energy Factor (MEF) is measured in cubic feet per kilowatt-hour per cycle. Water Consumption Factor (WCF) is measured in gallons per cycle per cylinder cubic feet. MEF and WCF statistics are according to Department of Energy (DOE) testing standards report by Intertek, an independent testing laboratory.

ECON-O-DRY SINGLELOAD AND STACKED DOUBLELOAD UNMATCHED DURABILITY

A perfect match to Econ-O-Wash top-load washers, Econ-O-Dry dryers – in singleload or stacked doubleload capacity – are not only easy to use, they dry laundry incredibly fast!

ROBUST DOOR AND CYLINDER

Equipped with an oversized door opening, Econ-O-Dry dryers make loading and unloading a snap using a sensible ergonomic design. The robust cylinder capacity takes on larger loads of laundry and provides improved tumble action through axial airflow technology—moving air more evenly through laundry items to get them dry faster!

EASY TO SERVICE & MAINTAIN

Designed for minimal maintenance and simplified serviceability, the drying tumbler features a lint filter that's easy to reach and clean, but doesn't get in the way. Moreover, when service is necessary, most components are accessible from the front of the machine. The motor, blower, heating element, gas valve and thermostats are serviceable through a lower front panel without disconnecting the door switch.

SAVE SPACE—DOUBLE PRODUCTION

By selecting the stack Econ-O-Dry model, on-premise laundries double drying capacity using half the space. The stack model offers two individually operable, single-pocket tumblers in one of the narrowest cabinets available (26.88 inches wide). This allows laundries to maximize space and productivity.

FLEXIBLE CONTROL

The dryer control offers fabric selection options including delicate, permanent press, no heat and normal, and an indicator light that illuminates when the machine is in use. A convenient timer enables the user to manually select dry time according to load type and size.

GAS OR ELECTRIC

Econ-O-Dry dryers are available in gas or electric heat—making them the right choice for any on-premise laundry. United Laboratories (UL) listed, Econ-O-Dry is built to last for years of trouble-free operation.



ECON-O-DRY PRODUCT SPECIFICATIONS

JDE807/JDG809 JSEM/JSGMN

Basket Volume	cu ft (dm3)	7.0 (199)	7.0 (199)
Net Weight	lbs (kg)		
	electric	135 (61)	135 (61)
	gas	140 (64)	140 (64)
Crated Weight	lbs (kg)		
	electric	145 (66)	145 (66)
	gas	150 (68)	150 (68)
Machine Width	inch (mm)	26.88 (683)	26.88 (683)
Machine Depth	inch (mm)	28 (711)	28 (711)
Machine Height	inch (mm)	44.38 (1127)	78.5 (1994)
Door Opening	inch (mm)	24.7 (628)	24.7 (628)
Shipping Dimensions	inch (mm)	29.5 x 30.5 x 45	29.5 x 30.5 x 45
		(749 x 775 x 1143)	(749 x 775 x 1143)
Exhaust Diameter	inch (mm)	4 (102)	4 (102)
Exhaust Air Flow	cfm (m3/min)	220 (6.23)	220 (6.23)
Basket Motor Power	Hp	1/3	1/3
Gas Heating	BTU/h (Kcal/h)	25,000 (6300)	25,000 (6300)
Gas Inlet Diameter	inch (mm)	3/8 NPT	3/8 NPT



CONTINENTAL GIRBAU INC. & GIRBAU GROUP

Continental Girbau Inc. (Continental) was established in 1995 as the North American subsidiary of the commercial laundry equipment manufacturer, Girbau Group, headquartered in Vic, Spain. Family owned, Girbau employs more than 600 people throughout its corporate headquarters in Vic and 15 subsidiaries throughout the world. It markets its industrial and commercial laundry products to more than 90 countries worldwide.

THE TOTAL LAUNDRY SOLUTION

Continental delivers the total laundry solution to vended, on-premise and industrial laundries throughout North America. As the provider of highly-efficient batch tunnel washers, washer-extractors, drying tumblers, feeders, ironers, folders and related machinery, Continental serves the complete laundry production and efficiency needs of virtually any application. Proven durable and reliable, Continental laundry systems are engineered for unrivaled productivity, efficiency and ease of use.

OUR MISSION: YOUR SUCCESS

Continental's mantra – "Our Mission: Your Success" – reflects the company's commitment to its distributors and customers. We offer robust laundry systems backed by unrivaled customer care.

WARRANTY

Econ-O-Wash and Econ-O-Dry are backed by an industry-leading 5/3-year ContinentalCare™ warranty.

FINANCING

Financing allows you to retain full ownership of your business and its assets while helping to preserve your cash, liquidity and revolving lines of credit for emergency use, working capital and other investments. Through CustomSelect™ Financing, Continental Girbau offers flexible financing and competitive fixed rates to all qualifying applicants.

ENVIRONMENTALLY FRIENDLY

Continental laundry products meet rigorous environmental and safety standards established by the International Organization for Standardization (ISO). Ever focused on laundry efficiency, Continental Girbau is a member of the U.S. Green Building Council (USGBC), a 501(c)(3) nonprofit that developed the Leadership in Energy and Environmental Design (LEED) Green Building Rating System.



CONTINENTALCARE™
BUY WITH COMPLETE CONFIDENCE

3-YR LIMITED PARTS WARRANTY
5-YR KEY COMPONENT WARRANTY



DISTRIBUTED BY:

