

SECTION II

SPECIFICATIONS

A. SPECIFICATIONS

MAXIMUM CAPACITY (DRY WEIGHT)		75 lb	34 kg
TUMBLER DIAMETER		37"	94 cm
TUMBLER DEPTH		36"	91.44 cm
TUMBLER MOTOR		1 hp*	0.75 kW
DOOR OPENING (DIAMETER)		21-1/2"	54.61 cm
TUMBLER VOLUME		22.4 cu ft	634.30 L
EXHAUST CONNECTION (DIAMETER)		8"	20.32 cm
AIRFLOW	60 Hz	1,000 cfm	28.32 cmm
	50 Hz	833 cfm	23.60 cmm
DRYERS PER 20'/40' CONTAINER		10 / 20	
DRYERS PER 48'/53' TRUCK		24 / 26	
S.A.F.E. WATER CONNECTION		3/4-11.5 NH	
GAS	VOLTAGE AVAILABLE	120-575V 1,3ø 2,3,4w 50/60 Hz	
	APPROX. WEIGHT (UNCRATED)	721 lb	327 kg
	APPROX. WEIGHT (CRATED)	771 lb	349.7 kg
	HEAT INPUT	175,000 Btu/hr	44,100 kcal/hr
	INLET PIPE CONNECTION	3/4" F.N.P.T.	

Shaded areas are stated in metric equivalents

2/5/04

* ALL reversing dryers are supplied with two (2) 3-phase (3ø) motors standard: a 1/2 hp (0.37 kW) blower motor and a 1/2 hp (0.37 kW) drive motor.

NOTE: The manufacturer reserves the right to make changes in specifications at any time without notice or obligation.