

Vended Quantum Gold Washer-Extractor Specifications

		SC20	SC30	SC40	
Control Option		Gold	Gold	Gold	
Capacity — lb (kg)		20 (9)	30 (13.6)	40 (18)	
Overall Width — in (mm)		26 (660)	29 (737)	30.6 (777)	
*Overall Depth — in (mm)		30.9 (785)	35.3 (897)	42.3 (1074)	
Overall Height — in (mm)		43 (1092)	45 (1143)	47.2 (1199)	
Cylinder Diameter — in (mm)		21 (533)	24 (610)	26.3 (668)	
Cylinder Depth — in (mm)		13.8 (351)	16 (406)	20.3 (516)	
Cylinder Volume — cu. ft (liters)		2.8 (79)	4.2 (119)	6.3 (178)	
Door Opening Size — in (mm)		11.6 (295)	14.3 (363)	16.3 (414)	
Door Bottom to Floor — in (mm)		14.4 (366)	14 (356)	14.6 (371)	
Water Inlet Connection — in (mm)		2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)	
Drain Diameter — in (mm)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)	
Drain Height to Floor — in (mm)		3.9 (99)	4.3 (109)	4.5 (114)	
Motor Power Consumption — HP (kW)		1 (0.75)	1 (0.75)	2 (1.5)	
Total # of Speeds		9	9	9	
Cylinder Speeds — RPM (G-Force)		Gentle 37 (0.4) Wash 51 (.8) Distribution 92 (2.5) Very Low 301 (27) Low 518 (80) Medium 579 (100) High 648 (125) Very High 710 (150) Ultra High 819 (200)	34 (0.4) 48 (.8) 86 (2.5) 282 (27) 485 (80) 542 (100) 606 (125) 664 (150) 766 (200)	33 (0.4) 46 (.8) 82 (2.5) 269 (27) 464 (80) 518 (100) 579 (125) 635 (150) 733 (200)	
** Voltage/Circuit Breaker — FLA	B X Y N	120/60/1 200-240/50-60/1/3 220-240/60/1/3 (Pump Drain Only) 440-480/50-60/3	15-9 15-4 (1 Ph) 15-3 (3 Ph) 15-4 (1 Ph) 15-2	15-12 15-7 (1 Ph) 15-4 (3 Ph) 15-7 (1 Ph) 15-4 (3 Ph) 15-3	20-15 15-7 (1 Ph) 15-4 (3 Ph) 15-7 (1 Ph) 15-4 (3 Ph) 15-3
Shipping Dimensions Approx. — in (mm)		Width 28 (711) Depth 33.8 (859) Height 49.4 (1255)	31.5 (800) 38.3 (973) 51.3 (1303)	32.5 (826) 43.5 (1105) 53.6 (1361)	
Net Weight — lb (kg)		340 (154)	440 (200)	540 (245)	
Shipping Weight — lb (kg)		380 (172)	480 (218)	580 (263)	
Slat Crate Shipping Weight — lb (kg)		460 (209)	580 (263)	680 (308)	
***Agency Approvals		cUL _{us}	cUL _{us}	cUL _{us}	

*Overall depth includes vacuum breaker to door handle.

**Circuit breaker and amp draw data shown are for models without electric heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines.

*** Agency approvals may vary depending on configuration. Consult factory for details. Steam connection requires 1/2" N.P.P.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.