

# Vended Quantum Gold Washer-Extractor Specifications

		SC60	SC80	SC100
Control Option		Gold	Gold	Gold
Capacity — lb (kg)		60 (27)	80 (36)	100 (45)
Overall Width — in (mm)		34.1 (866)	41.5 (1054)	41.5 (1054)
*Overall Depth — in (mm)		44.7 (1135)	47.1 (1196)	51.1 (1298)
Overall Height — in (mm)		49.9 (1267)	57.2 (1453)	57.2 (1453)
Cylinder Diameter — in (mm)		30 (762)	36 (914)	36 (914)
Cylinder Depth — in (mm)		22 (559)	21.9 (556)	25.9 (658)
Cylinder Volume — cu. ft (liters)		9.0 (255)	12.9 (365)	15.2 (430)
Door Opening Size — in (mm)		16.3 (414)	18.5 (470)	18.5 (470)
Door Bottom to Floor — in (mm)		14.9 (378)	17.9 (455)	17.9 (455)
Water Inlet Connection — in (mm)		2 x 0.75 (19)	2 x 0.75 (19)	2 x 0.75 (19)
Drain Diameter — in (mm)		1 x 3 (76)	1 x 3 (76)	1 x 3 (76)
Drain Height to Floor — in (mm)		4.9 (124)	5.1 (130)	5.1 (130)
Motor Power Consumption — HP (kW)		3 (2.2)	5 (3.7)	5 (3.7)
Total # of Speeds		9	9	9
Cylinder Speeds — RPM (G-Force)		Gentle 31 (0.4) Wash 43 (.8) Distribution 77 (2.5) Very Low 252 (27) Low 434 (80) Medium 485 (100) High 542 (125) Very High 594 (150) Ultra High 686 (200)	28 (0.4) 39 (.8) 70 (2.5) 230 (27) 396 (80) 443 (100) 495 (125) 542 (150) 626 (200)	28 (0.4) 39 (.8) 70 (2.5) 230 (27) 396 (80) 443 (100) 495 (125) 542 (150) 568 (165)
** Voltage/Circuit Breaker — FLA	B X Y N	120/60/1 200-240/50-60/1/3 220-240/60/1/3 (Pump Drain Only) 440-480/50-60/3	— 15-11 (1 Ph) 15-7 (3 Ph) — 15-4	— 20-15 (1 Ph) 15-9 (3 Ph) — 15-6
Shipping Dimensions Approx. — in (mm)		Width 37.5 (953) Depth 46.9 (1191) Height 56.3 (1430)	44 (1118) 54.5 (1384) 59.6 (1514)	44 (1118) 58.5 (1486) 59.6 (1514)
Net Weight — lb (kg)		680 (308)	1250 (567)	1280 (581)
Shipping Weight — lb (kg)		720 (327)	1300 (590)	1330 (603)
Slat Crate Shipping Weight — lb (kg)		840 (381)	1430 (649)	1460 (662)
***Agency Approvals		cUL <sub>us</sub>	cUL <sub>us</sub>	cUL <sub>us</sub>